



MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

**HousePure® Secure  
Tankless Water  
Heater Protection**

Part # WI-HP-SECURE-.75L (water entry left side)      Shipping Wt: 7 lbs.  
 Part # WI-HP-SECURE-.75R (water entry right side of Tankless Water Heater)      Ea. \$376.95  
 Utilizing Siliphos Polyphosphate  
 Recommended for all Tankless Water Heater Manufacturers



**LEVEL 1** Tankless Water Heater Scale Prevention. Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A 5-micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations. Features a 3/4" NPT inlet/outlet with a differential filter-change gauge for peace-of-mind.

**Includes mounting bracket, filter-change indicator gauge & filter-change spanner wrench**

**Max Descaling Service Flow Rate:** 9 gallons/minute

**Dimensions:** Width: 5.25" Height: 25.75" Depth: 5.5"

**Filter Capacity:** One year or when gauge or timer indicates change needed

**Water Temperature Range:** 40°F to 100°F

**Tools Required:** Teflon® tape, adjustable wrench, tube cutter, suitable pipe fittings and inlet gate valve

**NEW**  
Water entry RIGHT side  
**WI-HP-SECURE-.75R**

**Water, Inc filter change indicator included**  
Component Tested to NSF/ANSI Standard 42 for material requirements.

**NEW**  
Water entry RIGHT side  
**WI-HP-SECURE-.75R**

**HousePure® Secure  
Replacement  
Cartridge**

Part # WI-HP-SECURE-.75C      Shipping Wt: 1 lbs.  
 Utilizing Siliphos Polyphosphate      Shipping Wt: 19 lbs.  
 Recommended for all Tankless Water Heater Manufacturers      20-PK Ea. \$82.95



**Capacity:** One year or when gauge indicates change needed

**Dimensions:** Height: 20" Diameter: 2.5"

Replacement Cartridge for HousePure® Secure 3/4" tankless water heater filter system. The 5-micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

The HousePure® Secure cartridge should be changed annually or when gauge indicates a change is needed sooner.

Tested to NSF/ANSI Standard 42 for material requirements.

**Water, Inc filter change indicator included**

**MAXIMUM recommended line pressure for this product is 75 PSI.** Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)