

Model # 5700

CONTEMPORARY PULL DOWN FAUCET SPECS



Product Description

- Compatible with Reverse Osmosis filtration systems.
- Unique "PLP" positive lock holds spray head in place.
- Pre-positioned "Easy Pull" counterbalanced weight.
- Spray head extends 18" from spout.
- Toggle select spray or aerated stream.
- 1.75 gpm maximum flow rate with stream selected.
- Solid Brass or Stainless Steel construction.
- Single lever control hot/cold ceramic disk valve cartridge.
- Reversable/removable Hot & Cold indicator ring.
- Handle adjusts 45 degrees in either direction for clearance from backsplash.
- Braided connection hoses.
- Adjustable PTFE "Friction Lock" aids handle feel and prevents sag.
- 360 degree swivel spout.

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME A112.18.1
- CSA B125.1
- NSF 61
- CALGreen
- AB 1953

Finishes Available

FINISHES AVAILABLE: Almond - 01 Antique Brass - AB Antique Bronze - ABZ Antique Copper - AC American Bronze - AMB Antique Pewter - AP Black - 06 Black Nickel - BLN Black-Oil Rubbed Bronze - ORB Biscuit - 07 Caribbean Bronze - CB Chocolate Bronze - CHB Chrome - CH Distressed Antique Brass - DAB Distressed Antique Copper - DAC Distressed American Bronze - DAMB Distressed Antique Pewter - DAP Euro-White - EW Matte Black - MB Polished Brass - PB Polished Copper - PC Polished Gold - PG Polished Nickel - PN Satin Chrome - SC Satin Gold - SG Satin Nickel - SN Stainless Steel - SS*

DIMENSIONS MAY VARY AND ARE SUBJECT TO CHANGE. NO RESPONSIBILITY IS ASSUMED FOR USE OF SUPERCEDED OR VOIDED DATA

Tuscan Brass - TB Venetian Bronze - VB Weathered Brass - WB Weathered Copper - WC White - WT

*Contemporary Styles Only



41180 Raintree Court • Murrieta, CA 92562 • 1-888-304-0660 • 951-304-0520 • www.waterstoneco.com

- Max Counter Thickness 2-3/8"
- Recommended Install Hole Size 1-1/2"
- A. Spray Connection with 3/8" Compression Fitting
- B. Supply Hoses 20" Long with 3/8" Compression Fittings

