

F100139

Transitional Kitchen Faucet with Pulldown Spray

artos®

OPERATING SPECIFICATIONS



OPERATING TEMPERATURE

Maximum: 176°

OPERATING PRESSURE

Minimum: 20psi

Maximum: 125psi

Recommended: 25psi-70psi

FLOW RATE

1.8 USGPM @ 60psi

INSTALLATION DIMENSIONS

Max Countertop Thickness: 1 1/2"

Countertop Hole Dimension: 1-3/8"

Countertop Hole Stainless Steel Dimension: 1-3/4"

FEATURES

1-Hole Installation

Ceramic Disc Cartridge

Magnetic Docking Spray Head

STANDARDS

Certified to CUPC

Certified to AB1953

Certified to NSF/ANSI 61

ADA for lever handle

To view all standards, please visit product approvals in our learning hub at artos.us.com



Certified by
ICC-ES

1

WESTOVER, INC

4011 S 60TH ST, OMAHA, NE 68117

WWW.ARTOS.US.COM

T: 402-397-3344

All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

F100139

Transitional Kitchen Faucet with Pulldown Spray

artos®

PRODUCT DIMENSIONS

