PRODUCT SHEET

NOKORI 6331 63" x 31" x 24" (FREESTANDING)

Nokori's sleek and delicate lines inspire peace and calm-offering an authentic invitation to unwind.

PRODUCT NO.

MODEL	TN	IU	τι	JB
Freestanding	BNOLR	00T-XX	BNOLRF00N-XX	
THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system		\$		
Jets			40	
1 heated backrest			Included	
MiaPlus [®] Control* (not installed)			Included	
BU-Touch Control Application BUTOUCH NEW			\$	
Geysair®		Included		
AromaCloud®			N/A	
Illuzio Chromatherapy BCHRO6		\$		
TUB Soaker			\$	
AromaCloud®				N/A
Illuzio Chromatherapy BCHRO6		\$		
WarmTouchShell® BWTS		\$		
DOT control (not installed)			Included	with therapy
FEATURES				
Installation type			F	reestanding
No. of bathers	\$	Imp. gallo	ns	56
US gallons	68	Brass was	te kit	Included
INTEGRATED WASTE 8			xx	

INTEGRATED WASTE & OVERFLOW BOVERINI-XX White 01, Chrome 07, Brushed Nickel 09, Polished Nickel 10 Installed & Included STANDARD COLOR

White 01

OPTIONS (UPCHARGE APPLICABLE)		
FINISH		
UltraVelour Matte Finish (White only) BVEL		
INTEGRATED WASTE & OVERFLOW BOVERINI-XX		
Matte Black 19, Black Chrome 12, Satin Brass 18		
AIR INTAKE** & ISLAND TUB DRAIN™***		
Air intake & Island Tub Drain [™] BAIRISLD	\$	
Island Tub Drain [™] BISLDD	\$	
Cast Iron Island Tub Drain [™] BISLDDCI	\$	
Air intake BAIRINT	\$	
Air intake installation	\$	net
TILE FLANGE (specify position)		
Ordered with bath (not installed) BTILEN	\$	
Factory-installed. Right BTILER, Left BTILEL, Front BTILEF, Back BTILEB, Special installation BTILEO	\$	
IF REQUIRED BY CONSTRUCTION CODE		
Brass waste & overflow kit BDRCOB	\$	

Don't forget that this bath is available in **White only**.

If turbine is installed under the bath, please follow the installation instructions specified in the **Nokori Installation Manual**. * For TMU, control must be wall-mounted. Faucets must be freestanding

or wall-mounted. ** Air Intake is required if turbine is installed under the bath. *** An Island Tub Drain™ is required when there is no access under

*** An Island Tub Drain™ is required when there is no access under the bath.

TOTAL PRICE

Included




\$






NOKORI 6331 (FREESTANDING)

INSTALLATION





LETTER	DESCRIPTION	MEASURE
Α	Total length	63″
В	Bathing well length	47 1/4"
с	Total width	31″
D	Bathing well width	22 1/4"
E	Deck width	1 7/8″
F	Deck width at drain end	2″
G	Deck width at backrest	1 1/2"
н	Slope of backrest	24°
I	Outside edge to center of drain	10″
J	Height from drain to top of deck	20 7/8"
к	Maximum water level	17"
L	Total height	24″

Turbine position (TMU)

Indicates heated backrest (TMU)

(indicates WarmTouchShell® position (TUB)

TECHNICAL SPECIFICATIONS

Should be 70% of water capacity of TUB or greater.	Approx. shipping weight	
Access to the environment has a base to the 2011 Characteristic in the Access to the Access of	Turbine power	
line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is	Air heater	
	WARRANTY	
- Faucet must be freestanding or wall-mounted.	Controls-LED-Geysair*	
 Controls cannot be installed on the bath. The turbine should be remotely installed. 	Bath & turbine*	
 The turbine can also be installed under the bath. Please refer to the Nokori Installation Instructions. 	* Some restrictions apply www.bainu	
	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 8 sq. in. minimum. • The GEYSAIR must always be accessible and connected to the hot water supply (provide access) . • Faucet must be freestanding or wall-mounted. • Controls cannot be installed on the bath. • The turbine should be remotely installed . • The turbine can also be installed under the bath.	

provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

260 lbs
550 W
600 W
5 years
20 years

ultra.com/warranty



The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra[®] assumes no responsibility for preparatory work done prior to the product being on site.