



ENGINEERING EXCELLENCE

Cabrillo Series #4CB200T

SPECIFICATION SHEET

DESCRIPTION

- Single Handle Tub Trim Set
- Metal Handle
- Ceramic Disc Cartridge with Temperature Limit Stop
- Combo 1/2" IPS/Slip-On Tub Spout
- Tub Spout Escutcheon
- Color Match Sleeve and Retaining Ring

FINISHES

- PC PVD Polished Chrome
- BN PVD Brushed Nickel
- SS PVD Stainless Steel
- PN PVD Polished Nickel



#4CB200T SHOWN * ADA 

STANDARDS APPLICABLE

- ASME A112.18.1
- ANSI A117.1
- CUPC / IAPMO LISTED / ADA COMPLIANT

Model #: _____

Specific Features: _____

Project Name: _____

Submitted For: _____

| Model | Description | Finishes |
|----------|----------------------------|--|
| #4CB200T | Single Handle Tub Trim Set | <input type="checkbox"/> PC <input type="checkbox"/> Other__ |

| Required Valve | |
|----------------|--|
| | |

| | | |
|--------|--|------------------------------|
| #4020B | Single Handle Tub and Shower-Valve Set | <input type="checkbox"/> N/A |
|--------|--|------------------------------|




ENGINEERING EXCELLENCE

Pioneer:1-800-338-9468
 Commerce, CA 90040
 www.pioneerind.com
 Pioneer Industries, Inc. © 2013

DMSP4CB200T/REV. 12 2012
 Page 1 of 2

Installation Note:

Please refer to Installation Guide For this Product. Also Please refer to Installation Guide For the Rough-in Valve. Avoid Cross Flow Connections. Do not install a Shut off valve to any of the outlets. Install a 305 MM [12"] Straight Pipe with single elbow for bath between the rough-in valve and the tub spout. Cap the Shower Port for tub only installation.



Product Diagram



ENGINEERING EXCELLENCE

Pioneer: 1-800-338-9468
 Commerce, CA 90040
 www.pioneerind.com
 Pioneer Industries, Inc. © 2013